



SAW BLADES JIGSAW BLADES



D-JSB JIGSAW BLADES WOOD / METAL / ALUMINIUM

DESCRIPTION & USAGE:

Outstanding cutting performance in everyday applications. For cutting diagonally and horizontally through a wide range of materials.

T-SHANK FOR PRECISE JIGSAW FIT

PRECISION GROUND CUTTING EDGES

U-SHANK FOR UNIVERSAL POWER TOOL FIT



STANDARD

APPLICATION	SIMILAR TO	QTY PER PACK	LENGTH	SHANK	MATERIAL	D-JSB CODE / PRICE PER PACK
WOOD CUTTING - FINE FINISH	U101B	3	100 mm	U	HCS	D-JSB-001
WOOD CUTTING - FAST COARSE FINISH	T144D	3	100 mm	T	HCS	D-JSB-002
WOOD CUTTING - SCROLLER	T119B0	3	75 mm	T	HCS	D-JSB-003
WOOD CUTTING - FAST MEDIUM FINISH	T111C	3	100 mm	T	HCS	D-JSB-004
WOOD CUTTING - FAST SMOOTH FINISH	T101B	3	100 mm	T	HCS	D-JSB-005
WOOD CUTTING - FINE FINISH / DOWN CUT	T101BRF	3	75 mm	T	HCS	D-JSB-006
WOOD CUTTING - PROGRESSOR	T101D	3	100 mm	T	HCS	D-JSB-007
WOOD & LAMINATES - FINE	T301DL	2	100 mm	T	HCS	D-JSB-008
METAL CUTTING - 1.0-3.0 mm	T118A	3	75 mm	T	HSS	D-JSB-009
METAL CUTTING - 0.5-1.5 mm	T118G	3	75 mm	T	HSS	D-JSB-010
METAL CUTTING - 2.5-6.0 mm	T118B	3	75 mm	T	HSS	D-JSB-011
METAL CUTTING - 1.0-3.0 mm & PIPES - <65 mm	T318A	2	130 mm	T	HSS	D-JSB-012
ALUMINIUM - 3.0 - 15 mm & PVC - <30 mm	T127D	2	100 mm	T	HSS	D-JSB-013

DURO D-JSB CODE	APPLICATION
D-JSB-001	FAST, CLEAN CUT IN WOOD (UP TO 50 mm), PLYWOOD AND CHIPBOARD (UP TO 60 mm).
D-JSB-002	SOFTWOOD (5-50 mm), CHIPBOARD, WOOD CORE PLYWOOD, FIBRE BOARDS
D-JSB-003	SOFTWOOD (2-15 mm), PLYWOOD, CHIPBOARD, WOOD CORE PLYWOOD, FIBRE BOARDS - ESPECIALLY FOR CURVE CUTS
D-JSB-004	SOFTWOOD (4-50 mm), CHIPBOARD, WOOD CORE PLYWOOD, FIBRE BOARDS - QUICK CUT
D-JSB-005	SOFTWOOD, CHIPBOARD, WOOD CORE PLYWOOD, FIBRE BOARDS (3-30 mm) PLASTICS / EPOXY (DIA<30 mm)
D-JSB-006	HARDWOOD SUCH AS LAMINATING BOARDS (3-30 mm), KITCHEN WORKTOPS (<45 mm) - DOWN CUT
D-JSB-007	SOFTWOOD, CHIPBOARD, WOOD CORE PLYWOOD, FIBRE BOARDS (10-45 mm)
D-JSB-008	MEDIUM TO FINE STRAIGHT CUTS IN HARD & SOFT WOODS, PLYWOOD, LAMINATED PARTICLE BOARD & PLASTICS 6mm to 50mm
D-JSB-009	THIN SHEET METAL (1-3 mm)
D-JSB-010	VERY THIN SHEET METAL (0.5-1.5 mm)
D-JSB-011	MEDIUM THICK SHEET METAL (2.5-6 mm)
D-JSB-012	THIN SHEET METAL (1-3 mm), PIPES & PROFILES INC. ALUMINIUM (DIA <65 mm)
D-JSB-013	THIN TO THICK SHEET METAL (3-15 mm), PIPES & PROFILES (DIA <30 mm)

MATERIAL	DESCRIPTION
HCS	CARBON STEEL FOR USE WITH SOFTER MATERIALS
HSS	FULLY HARDENED HIGH SPEED STEEL FOR USE WITH HARDER MATERIALS

THE STANDARD-LINE FROM DURO, WITH A BROAD PRODUCT RANGE AND MANY TOOLS OFFERING PERFORMANCE LEVELS WELL ABOVE THE INDUSTRY STANDARD, THE OUTPUT OF THESE TOOLS IS VERY GOOD.

