

SAFETY DATA SHEET EVO-STIK GRIPFILL

According to Regulation (EC) No 1907/2006

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name EVO-STIK GRIPFILL

Product No. 18601, 18609, 18601Ax, 18624, 18638, 186064, 186071

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier

1.4. Emergency telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Liq. 2 - H225

Human health Skin Irrit. 2 - H315;STOT SE 3 - H336

Environment Aguatic Chronic 3 - H412

Classification (1999/45/EEC) Xi;R38. F;R11. R52/53, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word	Danger	
Hazard Statements		
	H225	Highly flammable liquid and vapour.
	H315	Causes skin irritation.
	H336	May cause drowsiness or dizziness.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary Statements		
	P102	Keep out of reach of children.
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing vapours.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

P264 Wash contaminated skin thoroughly after handling.

P370+378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for

extinction.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P332+313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.
P403+233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

Vapours are heavier than air and can travel long distances to a source of ignition Pilot lights can ignite the vapour

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

ACETONE			5-10%
CAS-No.: 67-64-1	EC No.: 200-662-2		Registration Number: 01-2119471330-49
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
EUH066		Xi;R36	
Eye Irrit. 2 - H319		R66	
STOT SE 3 - H336		R67	

NAPHTHA (PETROLEUM), HYDRODESULFURIZED LIGHT, DEAROMATIZED; <0.1% BENZENE 5-10%

CAS-No.: 92045-53-9 EC No.: 295-434-2

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 2 - H225 Xn;R65.
Skin Irrit. 2 - H315 Xi;R38.
STOT SE 3 - H336 F;R11.
Asp. Tox. 1 - H304 N;R51/53.
Aquatic Chronic 2 - H411 R67.

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, <0.1% BENZENE,

1-5%

CAS-No.: 64742-49-0 EC No.:

Classification (EC 1272/2008) Classification (67/548/EEC)

 Flam. Liq. 2 - H225
 Xn;R65.

 Skin Irrit. 2 - H315
 Xi;R38.

 STOT SE 3 - H336
 F;R11.

 Asp. Tox. 1 - H304
 N;R51/53.

 Aquatic Chronic 2 - H411
 R67.

N-HEXANE < 1%

CAS-No.: 110-54-3 EC No.: 203-777-6

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 2 - H225 F;R11

Skin Irrit. 2 - H315 Repr. Cat. 3;R62 Repr. 2 - H361f Xn;R65,R48/20

 STOT SE 3 - H336
 Xi;R38

 STOT RE 2 - H373
 R67

 Asp. Tox. 1 - H304
 N;R51/53

Aquatic Chronic 2 - H411

XYLENE 5-10%

CAS-No.: 1330-20-7 EC No.: 215-535-7 Registration Number: 01-2119488216-35

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 3 - H226 R10
Acute Tox. 4 - H312 Xn;R20/21
Acute Tox. 4 - H332 Xi;R38

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion

DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Promptly flush contaminated skin with water. Promptly remove clothing if soaked through and flush the skin with water. Get medical attention if irritation persists after washing.

Eye contact

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

No specific symptoms noted.

Ingestion

No specific symptoms noted.

Skin contact

No specific symptoms noted.

Eye contact

No specific symptoms noted.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Foam. Powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Fire creates: Toxic gases/vapours/fumes of: Carbon dioxide (CO2). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective equipment for fire-fighters

Wear self contained breathing apparatus

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus. Avoid breathing vapour

6.2. Environmental precautions

Prevent entry into drains and water courses.

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb onto sand, earth or abosorbent granules. Pick up with non-sparking tools and place into metal containers with sealable lids. Mark containers with details of hazards and store in designated area ready for disposal. Runoff or release to sewer, waterway or ground is forbidden.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Provide good ventilation. Avoid spilling, skin and eye contact. Avoid acids, moisture, and combustible materials.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Isolate from other materials. Store in tightly closed original container in a dry, cool and well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks. Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
N-HEXANE	WEL	20 ppm	72 mg/m3			
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment









Engineering measures

Provide adequate general and local exhaust ventilation. Explosion-proof general and local exhaust ventilation.

Respiratory equipment

Respiratory protection must be used if air contamination exceeds acceptable level. Wear mask supplied with: Gas cartridge suitable for organic substances.

Hand protection

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Liquid

Odour Characteristic.

Relative density 1.18

Flash point (°C) -20 CC (Closed cup).

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not available.

Hazardous Polymerisation

Unknown.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Not known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

Vapour may irritate respiratory system or lungs. Vapour may affect central nervous system and cause headache, discomfort, vomiting or intoxication.

Ingestion

May cause discomfort if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact

Irritating to skin.

Eye contact

May cause temporary eye irritation.

Health Warnings

Pneumonia may be the result if vomited material containing solvents reaches the lungs.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product contains a substance which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

No data available

12.2. Persistence and degradability

Degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

This material is classified as special waste as defined by Special Waste Regulations 1996 and must be disposed of by an authorised contractor

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1133 UN No. (IMDG) 1133 UN No. (ICAO) 1133

14.2. UN proper shipping name

Proper Shipping Name ADHESIVES

14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

IMDG Class 3

ICAO Class/Division
Transport Labels



3

14.4. Packing group

ADR/RID/ADN Packing group III
IMDG Packing group III
ICAO Packing group III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

14.6. Special precautions for user

EMS F-E, S-D
Emergency Action Code •3YE
Hazard No. (ADR) 33
Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations. EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

General information

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services. Information Sources

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision. This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

Issued By Approved LJ
Revision Date June 2014

Revision 3

Date November 2011

Risk Phrases In Full

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable
R36 Irritating to eyes.
R38 Irritating to skin.

R62 Possible risk of impaired fertility.

R66 Repeated exposure may cause skin dryness or cracking.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.
H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.

H373 May cause damage to organs << Organs>> through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.